U.S. Patent Application No.: 10/582,426

Filing Date: 08 June 2006

First Named Inventor: George Gallagher

AMENDMENTS TO THE CLAIMS

Please cancel claims 22 - 35.

36. (Currently amended) The syringe driver assembly of claim 35. A syringe driver assembly

for imparting translational movement to a syringe plunger, comprising:

a. a motor driven unthreaded shaft,

b. at least one bearing mounted obliquely to the shaft and having at least one point

of contact therewith, and

c. an actuator linked to at least one of the bearings for contacting a thumbplate of the

plunger, wherein rotation of the shaft causes movement of the actuator-linked

bearing along the shaft to affect movement of the actuator;

wherein at least three bearings are provided with alternate bearings being mounted at the same

angle relative to the shaft and adjacent bearings being mounted at an opposing angle relative to

the shaft;

wherein the inclined bearings are symmetrically spaced in one plane perpendicular to the shaft

axis and the outer races of the bearings make radial contact with the shaft;

wherein the bearing is spring loaded;

wherein the carriage is connected to the actuator; and

wherein the carriage is provided with guides.

37. (Currently Amended) The syringe driver assembly of claim 36 further comprising: means

for manually disengaging

3

U.S. Patent Application No.: 10/582,426

Filing Date: 08 June 2006

First Named Inventor: George Gallagher

a. <u>a carriage with a movable portion having at least one of the bearing mounted</u> therein; and

b. a manually actuable push spring contacting the carriage movable portion to

disengage at least one bearing to enable sliding movement independently of the

shaft upon manual actuation of the push spring.

38. (Currently Amended) The syringe driver assembly of claim 37 36 wherein at least one

bearing is spring-loaded with respect to the shaft and operation of the spring mechanism

disengages that bearing from the shaft.

39. (Currently Amended) The syringe driver assembly of claim 37 36 wherein manual

disengagement is affected by movement of a housing containing a bearing in a direction

transverse to the shaft to lift the bearing from the shaft.

40. (Previously Presented) The syringe driver assembly of claim 39 further comprising a cam

and lever for lifting the bearing from the shaft.

Please cancel claims 41 and 42.

4